



Dart Aerospace Ltd.
1270 Aberdeen St
Hawkesbury, ON
K6H 1K7
Canada

Tel (613) 632-5200
Fax 613 632-5246

D3012-3
Job Sheet 214115



Part No: D3012-3

Job Qty: 12 pcs

Part Name: Decal



Part Weight: 0 lbs

Status: New

Priority: Medium

File Created: 10/16/20

Job Tracking No:

Pre Date: 11/13/20

Created By: Marie Lajouesse

Type: Stock

Description:

Note: DWG REV A IPP A 01.04.06 New Issue EC

Ship Via:

Bill of Materials

Job Routing

Op No	Operation	Qty	Start Date	Due Date	Standard Setup Run Hrs Hrs	Workcenter / Supplier	Lead Time	Sign-off
100	Purchasing	12 pcs	11/13/20	11/13/20	0.00 0.00	Purchasing - 1		 OCT 27 2020
						Purchasing - 2		
						Purchasing - 3		
110	Packaging - 1 Receive - B4E	12 pcs	11/13/20	11/13/20	0.00 0.00	Packaging 2 - 1 - B4B		 OCT 27 2020
						Packaging 2 - 2 - B4B		
						Packaging 2 - 3 - B4B		
						Packaging 2 - 5 - B4B		
						Packaging 2 - 4 - B4B		
						Packaging 2 - 6 - B4B		
						Packaging 2 - 7 - B4B		
						Packaging 2 - 8 - B4B		
						Packaging 2 - 9 - B4B		
						Packaging 2 - 10 - B4B		
						Packaging 2 - 11 - B4B		
						Packaging 2 - 12 - B4B		
						Packaging 2 - 13 - B4B		
						Packaging 2 - 14 - B4B		
						Packaging 2 - 15 - B4B		
						Packaging 2 - 16 - B4B		
						Packaging 2 - 17 - B4B		
						Packaging 2 - 18 - B4B		
						Packaging 2 - 19 - B4B		
						Packaging 2 - 20 - B4B		



Container No: S308673



Part: D3012-3
Job No: 214115
Serial No/Batch: S308673
Revision:
Inspector:
Exp Date: 10/22/2021
Instructions: Various STC's

Dart Aerospace Ltd.
1270 Aberdenn Street
Hawkesbury, ON K6A 1K7
CANADA
TEL: 1 813 632-5200
Email: sales@dartaero.com
www.dartaerospace.com

Date: 10/27/20

Kimberley Guerin



Dart Aerospace Ltd.
1270 Aberdeen Street
Hawkesbury, ON K6A 1K7
CANADA
TEL: 1 613 632-5200
Email: sales@dartaero.com
www.dartaerospace.com

Container No: S308673



Part: D3012-3

Job No: 214115

Serial No/Batch: S308673

Revision:

Inspector:

Exp Date: 10/22/2021

Instructions: Various STC's

Date: 10/27/20

Plex 10/20/20 12:57 PM User: Guerin.Kimberley

				B4B	
				Packaging 2 - 21 - B4B	
				Packaging 2 - 22 - B4B	
				Packaging 2 - 23 - B4B	
				Packaging 2 - 24 - B4B	
				Packaging 2 - 25 - B4B	
				Packaging 2 - 26 - B4B	
				Packaging 2 - 27 - B4B	
				Packaging 2 - 28 - B4B	
				Packaging 2 - 29 - B4B	
				Packaging 2 - 30 - B4B	
				Packaging 2 - 31 - B4B	
				Packaging 2 - 32 - B4B	
				Packaging 2 - 33 - B4B	
				Packaging 2 - 34 - B4B	
				Packaging 2 - 35 - B4B	
				Packaging 2 - 36 - B4B	
				Packaging 2 - 37 - B4B	
120	QC 6	12 pcs	11/13/20	0.00 0.00	QC 6 - 9
					QC 6 - 68
					QC 6 - 61
					QC 6 - 40
					QC 6 - 81
					QC 6 - 82
130	Packaging 3-1 - Stock - B4B	12 pcs	11/13/20	0.00 0.00	Packaging 3 - 1 - B4B
					Packaging 3 - 2 - B4B
					Packaging 3 - 3 - B4B
					Packaging 3 - 4 - B4B
					Packaging 3 - 5 - B4B
					Packaging 3 - 6 - B4B
					Packaging 3 - 7 - B4B
					Packaging 3 - 8 - B4B
					Packaging 3 - 9 - B4B
					Packaging 3 - 10 - B4B
					Packaging 3 - 11 - B4B
					Packaging 3 - 12 - B4B
					Packaging 3 - 13 - B4B
					Packaging 3 - 14 - B4B
					Packaging 3 - 15 - B4B
					Packaging 3 - 16 -

DAS
81
9-89

OCT 30 2020

DAS
28
9-89

OCT 30 2020

				B4B	
				Packaging 3 - 17 - B4B	
				Packaging 3 - 18 - B4B	
				Packaging 3 - 19 - B4B	
				Packaging 3 - 20 - B4B	
				Packaging 3 - 21 - B4B	
				Packaging 3 - 22 - B4B	
				Packaging 3 - 23 - B4B	
				Packaging 3 - 24 - B4B	
				Packaging 3 - 25 - B4B	
				Packaging 3 - 26 - B4B	
				Packaging 3 - 27 - B4B	
				Packaging 3 - 28 - B4B	
				Packaging 3 - 29 - B4B	
				Packaging 3 - 30 - B4B	
				Packaging 3 - 31 - B4B	
				Packaging 3 - 32 - B4B	
				Packaging 3 - 33 - B4B	
				Packaging 3 - 34 - B4B	
				Packaging 3 - 35 - B4B	
				Packaging 3 - 36 - B4B	
				Packaging 3 - 37 - B4B	
140	QC 21 - SA	12 pcs	11/13/20	0.00 0.00	QC 21 - SA - 21
					QC 21 - SA - 70
					QC 21 - SA - 9
					QC 21 - SA - 77
					QC 21 - SA - 28

DAS
21
9-8-

OCT 30 2020

OCT 30 2020

Part Op 100 - (Purchasing) Issue P/O: _____
 Descriptions: 110 - (Receive & Inspect for Damage & Mat'l Certs) Ensure Material Release Note is attached
 120 - (QC6- All purchased or subcontracted products)
 130 - (Identify as per dwg & Stock Location: _____)
 140 - (QC21- Final Inspection - Work Order Release)

PO Details

Studio de Lettrage 2001 (stu002-vc)



PO No: POHB047400

Line No: 3

Job BOM				
Part / Item	Component Name	Quantity	Operation	Container
D3012-3P	Decal	12 pcs (1 ea)	100-Purchasing	S308672
Job Allocations				
Operation	Component Part	Required	Inventory	Allocated
100-Purchasing	D3012-3P	12	0	0
Part Specifications				
Specifications could not be found.				

Plex 10/20/20 12:57 PM Dart.Guerin.Kimberley



Via:	Ground
Pymt Terms:	Net 30
Freight Terms:	
Special Comments:	

Grand Total: \$320.00

https://www.plexonline.com/0F9005DA-C94B-47C7-8A83-EE7796900981/Plexus_Control/Report_Viewer_2.asp?rv=u%1E..%2FPurchasing%2FPO_P... 1/1

*** CERTIFICATE of CONFORMITY ***				
Manufacture: <u>Studio 52</u>				
Purchase order #:	Packing Slip#	Part #:	Drawing Rev:	Serial/Batch:
<u>HB047400</u>	<u>WP#27892</u>		<u>1 + A</u>	
Description (Part Name): <u>RBEM671V2000101-5P</u> <u>D3012-1P, D3012-3P, D3012-5P</u>				Quantity: <u>6, 12, 12, 12</u>
Certification: We hereby certify that:				PLEASE CHECK BOX IF REQUIRED
1. The above listed items were manufactured and/or inspected in accordance with applicable supplied drawings and/or specifications.				☒
2. All work was accomplished in accordance with the Dart Aerospace Ltd. purchase order.				☒
3. Results of all inspections, chemical or physical test, as well as other evidence, which shows the acceptability of raw materials, parts and/or assembly components are on file and available for inspection at any time.				☒
4. All material certification or copies of purchase orders of the material used to manufacture this component have been attached to this document.				☒
Record Expiry Date of Materials: <u>October 22, 2021</u>				
Authority: <u>3m + Avey</u>				
Approval:		Date: (yyyy/mm/dd)		
<u>Valerie Yang</u>		<u>2020/10/22</u>		
Signature:		Title:		
<u>Val</u>		<u>Office Admin.</u>		

DAS
81
9-89

studio sl2

210 Main West
Hawkesbury, Ontario K6A 2H6
Canada

INVOICE

Invoice No.: 50229
Date: 10/22/2020
Ship Date:
Page: 1
Re: Order No.

Sold to:

Dart Aerospace Ltd

1270 Aberdeen
Hawkesbury, Ontario
K6A 1K7

Ship to:

Dart Aerospace Ltd

1270 Aberdeen
Hawkesbury, Ontario
K6A 1K7

825007651RT0001

Quantity	Description	Base Price	Disc. %	Unit Price	Tax code	Amount
6	RBEM671V2000101-5P.	13.3333		13.3333	H	80.00
12	D3012-1P.	6.6667		6.6667	H	80.00
12	D3012-3P.	6.6667		6.6667	H	80.00
12	D3012-5P.	6.6667		6.6667	H	80.00
	PO#HB047400 ✓					
	Attn: Kim Guerin					
	Subtotal:					320.00
	H - HST					
	HST					41.60
RECEIVED OCT 23 2020 DART AEROSPACE LTD. Thank you for your business / Merci de faire affaire avec nous						

Shipped By:	Tracking Number:	HST: 825007651RT0001	Total Amount	361.60
Comment: WO27892			Amount Paid	0.00
Sold By:			Amount Owing	361.60

PRODUCT DATA SHEET



Avery IPM I™ 7112

issued: 15/04/2002

Introduction

Avery IPM I 7112 is a white monomeric calendered removable self-adhesive vinyl for use on the Idanit 162Ad inkjet printer, providing good machine runnability. Because of its cost efficiency and good removability, Avery IPM I 7112 is recommended for a wide range of short term applications on flat substrates requiring easy and clean removal.

Description

Film : 100 micron gloss white monomeric calendered vinyl
Adhesive : **removable**, acrylic based
Backingpaper : kraft paper, 140 g/m²

Conversion

Avery IPM I 7112 is specially developed for use on the Idanit 162Ad and Idanit Novo inkjet printer and has been officially approved by Idanit using BL and Magic inks.

Uses

- Interior & exterior signs.
- Window decoration.
- Temporary promotional and point of sale advertising and all.
- applications to flat or regular surfaces that require removability.

Features

- Good printability and handling on Idanit 162Ad.
- Easy conversion.
- Most economical solution for short term outdoor graphics.
- Easy and clean removal (up to 1 year).



www.averygraphics.com

Graphics Division
Rijndijk 86, P.O. Box 118
2304 ZG Hazerswoude The Netherlands
Tel +31 71 3421500 - Fax +31 71 3421538

PRODUCT CHARACTERISTICS

Avery® IPM I™ 7112

Physical properties

Features	Test method ¹	Results
Caliper, facefilm	ISO 534	100 micron
Opacity	ISO 2471	92%
Dimensional stability	DIN 30646	0.3 mm max.
Adhesion, initial	FINAT FTM-1, stainless steel	225 N/m
Adhesion, ultimate	FINAT FTM-1, stainless steel	400 N/m
Flammability		Self extinguishing
Shelf life	Stored at 22° C/50-55 % RH	2 years
Removability		up to 1 year*
*Not when applied to: Nitrocellulose paints, ABS, Polystyrene, screenprinting inks (fresh), certain types of PVC		
Durability, unprinted	Vertical exposure	2 years

Temperature range

Features	Results
Minimum application temperature:	0° C
Temperature range:	- 40 to +100 °C

Important

Information on physical and chemical characteristics is based upon tests we believe to be reliable. The values listed herein are typical values and are not for use in specifications. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of this material to their specific use. All technical data are subject to change.

Warranty

Avery® branded materials are manufactured under careful quality control and are warranted to be free from defect in material and workmanship. Any material shown to our satisfaction to be defective at the time of sale will be replaced without charge. Our aggregate liability to the purchaser shall in no circumstances exceed the cost of the defective materials supplied. No salesman, representative or agent is authorised to give any guarantee, warranty, or make any representation contrary to the foregoing.

All Avery® branded materials are sold subject to the above conditions, being part of our standard conditions of sale, a copy of which is available on request.

1) Test methods

More information about our test methods can be found on our website.

2) Durability

The durability is based on middle European exposure conditions. Actual performance life will depend on substrate preparation, exposure conditions and maintenance of the marking. For instance, in the case of signs facing south; in areas of long high temperature exposure such as southern European countries; in industrially polluted areas or high altitudes, exterior performance will be decreased.



**AVERY
DENNISON**

www.averydennison.com

Graphics Division

Rijndijk 86, P.O. Box 118
2304 ZG Hazerswoude The Netherlands
Tel +31 71 3421500 - Fax +31 71 3421538

IJ35-10 IJ35-20

Quick Links

[3M Graphics Warranties](#)
[Technical Information Selector](#)
[Safety Data Sheets \(SDS\)](#)
[Flammability \(ASTM E84 Reports\)](#)
[Videos](#)

Product Description

- For Solvent, Eco-Solvent UV and Latex Inkjet Printing and Screen Printing
- 3.2-mil vinyl film

Product Features

- Available in gloss and matte finishes
- Pressure-sensitive adhesive
- Permanent
- Expected Performance Life of 5 years (unwarranted period for unprinted film with no graphic protection, applied to a flat, vertical, outdoor surface)

Recommended Types of Graphics and End Uses

- Short to long-term, indoor and outdoor promotional graphics
- Signs, trade show and point-of-purchase displays
- Exhibits and architectural applications

Graphic Protection

Graphic protection can improve the appearance, performance and durability of your graphic. Always use only the graphic protection options recommended in this Bulletin for this film.

- [3M™ Scotchcal™ Gloss Overlamine 8508](#)
- [3M™ Scotchcal™ Luster Overlamine 8509](#)
- [3M™ Scotchcal™ Matte Overlamine 8510](#)

Characteristics

These are typical values for unprocessed product. Processing may change the values.

Physical Characteristics

Characteristic	Value
Material	Vinyl
Film Color	White, opaque
Thickness	Without adhesive: 3.25 mil (0.081 mm) With adhesive: 4.0 mil (0.102 mm)
Adhesive	Pressure sensitive
Adhesive Color	Gray
Liner	Polyc coated paper
Flammability	ASTM E84 reports: IJ35-10 and IJ35-20 , or go to the On-line Product Catalog at 3Mgraphics.com

Application Characteristics

Characteristic	Value
Finished Graphic Application Recommendation	Surface type: Smooth, flat and simple curved surfaces Substrate type: Metal, rigid plastic and painted surfaces Application temperature: 40° – 100°F (4° – 38°C) air and substrate Application method: Dry
Temperature Range After Application	-59 °F to +192 °F (-50 °C to +90 °C) (not for extended periods of time at the extremes)
Graphic Removal	Permanent

Warranty Information

Warranty Coverage Overview

The warranty coverage for eligible graphics is based on the user both reading and following all applicable and current 3M Graphics Product and Instruction Bulletins. The warranty period for eligible graphics is as stated in the 3M Graphics Warranties Matrices at the time that the film was purchased. Information found at 3MGraphics.com/warranties includes:

- [3M Graphics Warranties Bulletin](#)
 - This bulletin contains information on limitations and exceptions, and warranty period reductions for 3M Graphics Warranties. The warranty period may be reduced and stipulations may apply for certain constructions, applications, and graphic exposures as covered in this Bulletin.
- [3M Graphics Warranties Selector](#)
 - Use this selector to search for your vertical warranty period by product type, ink type, film name, and/or ink/printer platform.
- [U.S. Desert Southwest Region Map](#)
 - Use this map of hot, arid desert areas to determine if you are subject to reduced warranted durabilities.

The warranties set forth in this Bulletin are made in lieu of all other express or implied warranties, including any implied warranty of merchantability, fitness for a particular purpose, or arising out of a course of dealing, custom, or usage of trade.

3M Basic Product Warranty

3M Graphics Products are warranted to be free of defects in materials and manufacture at the time of shipment and to meet the specifications stated in its applicable 3M Graphics Product Bulletin and as further set forth in the [3M Graphics Warranties Bulletin](#).

Limited Remedy

The limited remedy applicable to each warranty is addressed in the 3M Graphics Warranties Bulletin found at 3MGraphics.com/warranties.

Limitation of Liability

Except where prohibited by law, 3M SHALL NOT UNDER ANY CIRCUMSTANCES BE LIABLE TO PURCHASER OR USER FOR ANY DIRECT (EXCEPT FOR THE LIMITED REMEDY PROVIDED IN THE 3M GRAPHICS WARRANTIES BULLETIN), INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, LABOR, NON-3M MATERIAL CHARGES, LOSS OF PROFITS, REVENUE, BUSINESS, OPPORTUNITY, OR GOODWILL) RESULTING FROM OR IN ANY WAY RELATED TO 3M'S GRAPHICS PRODUCTS, SERVICES, or THIS BULLETIN. This limitation of liability applies regardless of the legal or equitable theory under which such losses or damages are sought.

Additional Limitations

See the 3M Graphics Warranties Bulletin at 3MGraphics.com/warranties, for terms, additional limitations of your warranty, if any, information on reduced warranties for different exposures, and limitations of liability.

Factors that Affect Graphic Performance Life

The actual performance life of a graphic is affected by:

- the combinations of graphics materials used.
- complete ink drying or curing.
- selection, condition and preparation of the substrate.
- surface texture.
- application methods.
- angle and direction of sun exposure.
- environmental conditions.
- cleaning or maintenance methods.

Graphics Manufacturing

CAUTION

Before using any equipment, always read the manufacturer's instructions for safe operation.

Inkjet Printing

Always read and follow the ink manufacturer's written instructions on usage.

- **Sheeted film:** When used on a flat-bed inkjet printer, sheeted film may produce printing defects.
- **Ink limiting:** The recommended maximum ink limit is 250%.
- **If sheeted or stacked graphics will be stored:** If you plan to store sheeted and stacked finished graphics for an extended period of times, leave an unprinted margin (about 1/4 inch) to allow for possible shrinkage before trimming the graphic.

Do not exceed the recommended total ink coverage for the ink series used on this film. Having too high a total physical ink amount on the film results in media characteristic changes, incomplete drying, overlamine lifting, and/or poor graphic performance.

Completely Dry Graphics

IMPORTANT NOTE

Incomplete drying or curing can result in graphic failure including curling, increased shrinkage and adhesion failure, which are not covered under any 3M Graphic Warranty.

See the ink's 3M Product and Instruction Bulletin for more details.

Screen Printing

Formulations and processing conditions can affect ink durability. Refer to the Product and Instruction Bulletins for your ink for limitations and proper usage.

Cutting

See [3M Instruction Bulletin 4.1](#) for Sheeting, Scoring and Film Cutting details.

Graphic Protection

Graphic protection may improve the appearance, performance and durability of the graphic. Click on the graphic protection options listed in Product Bulletin or see the [3M Graphics Market Product Catalog](#), for more information.

IMPORTANT NOTE

During installation, scratches may occur on films without graphic protection.

Application and Installation

In addition to other 3M Bulletins specified in this document, the following Bulletins provide details that you may need to successfully apply a graphic.

- [3M Instruction Bulletin 4.22](#). Hot and Cold Roll Lamination for 3M Overlaminates.
- [3M Instruction Bulletin 5.1](#) Select and Prepare Substrates for Graphic Application
- [3M Instruction Bulletin 5.19](#). Lamination, Application & Maintenance of Floor Graphics. Complete the Surface Preparation procedure found in this Instruction Bulletin prior to applying a graphic to a surface.
- [3M Instruction Bulletin 5.5](#) Application, General Procedures for Interior and Exterior Dry Application
- [3M Instruction Bulletin 6.5](#) Storage, Handling, Maintenance, and Removal of Films and Sheetings

Pressure-sensitive Adhesive

This film has a pressure-sensitive adhesive. It bonds to the surface even with light pressure and cannot be repositioned.

Maintenance and Cleaning

Use a cleaner designed for high-quality painted surfaces. The cleaner must be wet, non-abrasive, without solvents, and have a pH value between 3 and 11 (neither strongly acidic nor strongly alkaline). See [3M Instruction Bulletin 6.5](#) for details.

Shelf Life, Storage and Shipping

Shelf Life

The shelf life is **never more than 2 years** from the date of manufacture on the original box.

If you process the film, the shelf life is changed to **1 year** from the processing date, but not later than the 2 year maximum from the manufacturing date.

Storage Conditions

- 90 °F (32 °C) maximum
- Out of sunlight
- Clean, dry area
- Original container
- Bring the film to print room temperature before using

Shipping Finished Graphics

Flat, or rolled printed side out on 5 inch (13 cm) or larger core. This helps prevent the liner, if used, from popping off.

Health and Safety

CAUTION

When handling any chemical products, read the manufacturer's container labels and the Safety Data Sheets (SDS) for important health, safety and environmental information. To obtain SDS sheets for 3M products go to 3M.com/SDS, or by mail or in case of an emergency, call 1-800-364-3577 or 1-651-737-6501.

When using any equipment, always follow the manufacturer's instructions for safe operation.

Bulletin Change Summary

For the most current 3M Technical Information available to successfully use this product, please view this Bulletin electronically and click on the blue underlined links to view the relevant documents.

Release J, NOV-2016:

- Updated Thickness. See "Physical Characteristics" on page 1.

3M Commercial
Solutions
3M Center
Building 220-12E-04
St. Paul, MN 55144-1000
Phone 1-888-328-3908
Web 3M.com/Graphics

3M Canada
PO Box 5757
London, ON N6A 4T1
1-800-265-1840
Fax 519-452-6245

3M México S.A. de C.V.
Av. Santa Fe No. 55
Col. Santa Fe, Del. Alvaro
Obregón
México D.F. 01210
General 5255-5270-0400
Fax 5255-5270-2277

3M Puerto Rico, Inc.
350 Chardon Avenue
Suite 1100
San Juan, PR 00918
General 787-620-3000
Fax 787-620-3018

3M and Scotchcal are trademarks of 3M Company. All other trademarks are the property of their respective owners.

